



El-galvaniseret øjeskrue - acc. to Din 580



Vare nr.	Dim. d1 mm	Dim. d2 mm	Dim. d3 mm	Dim. d4 mm	Dim. h mm	Dim. l mm	Dim. k mm	Brudstyrke ca. ton	Vægt kg/%
801006	6	20	36	20	36	13	8	0,35	5,0
801008	8	20	36	20	36	13	8	0,70	6,0
801010	10	25	45	25	45	17	10	1,15	11,0
801012	12	30	54	30	53	20	12	1,70	18,0
801016	16	35	63	35	62	27	14	3,50	28,0
801020	20	40	72	40	71	30	16	6,00	45,0
801024	24	50	90	50	90	36	20	9,00	87,0
801030	30	65	108	60	109	45	24	16,0	166,0
801036	36	75	126	70	128	54	28	23,0	265,0
801048	48	100	166	90	168	68	38	43,0	638,0

El-galvaniseret øjemøtrik - acc. to Din 582



Vare nr.	Dim. d1 mm	Dim. d2 mm	Dim. d3 mm	Dim. d4 mm	Dim. h mm	Dim. k mm	Brudstyrke ca. ton	Vægt kg/%
801106	6	20	36	20	36	8	0,35	4,8
801108	8	20	36	20	36	8	0,70	5,0
801110	10	25	45	25	45	10	1,15	9,0
801112	12	30	54	30	53	12	1,70	16,0
801116	16	35	63	35	62	14	3,50	24,0
801120	20	40	72	40	71	16	6,00	36,0
801124	24	50	90	50	90	20	9,00	72,0
801130	30	65	108	60	109	24	16,0	132,0
801136	36	75	126	70	128	28	23,0	208,0
801148	48	100	166	90	168	38	43,0	502,0