










Vare Nr.	Længde Mtr	 Lige Løft	 Sanset løft	 U-løft (Parallelt)	 U-løft 0° – 45°	 U-løft 45° – 60°	 2-strengt 0° – 45°	 2-Strengt 45° – 60°	 2-Strengt 0° – 45°	 2-strengt (sanset) 45° – 60°
		Lastfaktor 1	Lastfaktor 0.8	Lastfaktor 2.0	Lastfaktor 1.4	Lastfaktor 1.0	Lastfaktor 1.4	Lastfaktor 1.0	Lastfaktor 1.12	Lastfaktor 0.8
		WLL T	WLL T	WLL T	WLL T	WLL T	WLL T	WLL T	WLL T	WLL T
R12T0,5/1M	0,5	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T1/2M	1	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T1,5/3M	1,5	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T2/4M	2	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T2,5/5M	2,5	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T3/6M	3	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T3,5/7M	3,5	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T4/8M	4	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T5/10M	5	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T6/12M	6	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T10/20M	10	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60
R12T12/24M	12	12.00	9.60	24.00	16.80	12.00	16.80	12.00	13.44	9.60

